lammina

8 AL **SUPERLIGHT**

Aluminum Tenders



Overal Beam Inside Length : 8'5"/ 2.56m

Number of Chambers

Shaft Length : 15" / 38.1cm

: 4'9"/ 1.45m

Person Capacity : 4 RDC Design Category : C

Inside Beam

: 2'/ 0.62m

: 5′10″/1.79m

Recommended HP : 4hp/3.0kw

: 73lb / 33kg

Tube Diameter : 16"/ 0.40m Maximum HP : 6hp / 4.5kw

жш A & ∢ < \vdash \blacksquare

SП

ωш 0 ш

ے

S

- Deep "V" Marine Grade Aluminum Hull
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
 3 Aluminum Davit Lifting Points
- 3 Aluminum Davic EnDeck Drain with Plug

- Orca(CSM) Five Layer Coated Fabric
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves Raised Single Rub Rail 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes

- 2 Inside Bow Single Orca(CSM) Fabric Handles on Tubes 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing SeatOarlock Bases

Weight

- Telescopic Oars with Aluminum Shaft

- Paddle Holders Hand Pump Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

Tube Chaps Boat Cover

- Chock Set

- Bow Step with Fold Down Stainless Steel cleat
- Lateral Fold Down Stainless Steel Cleat



21 Rowland Street, Slacks Creek. Qld 4127 Ph 3808 1988 www.marinesafe.com.au



lammina

9 AL **SUPERLIGHT**

Aluminum Tenders



S ш ؎ S

Overal Length Number of Chambers Shaft Length 9'1"/ 2.76m : 15" / 38.1cm **Overal Beam Person Capacity** : 4 : 4'9"/ 1.45m RDC Design Category : C Inside Length : 6'3"/ 1.90m Weight : 79lb / 36kg Inside Beam : 2'2"/ 0.66m Recommended HP : 8hp / 6.0kw Tube Diameter : 16"/ 0.40m Maximum HP : 10hp / 7.5kw

2 жш A A **4 4** \vdash \sqcup SН

- Deep "V" Marine Grade Aluminum Hull
- Heavy Duty Transom Knee
- Non Skid Rubber Floor Panels
- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
 3-4 Aluminum Davit Lifting Points
- Deck Drain with Plug

- Orca(CSM) Five Layer Coated Fabric
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Single Rub Rail 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases

- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

Zœ д ш

ОШ

- Bow Locker/ Seat
- Tube Chaps
- Boat Cover

- Chock Set
- Bow Step with Fold Down Stainless Steel cleat
- Lateral Fold Down Stainless Steel Cleat



lammina

9.5AL SUPERLIGHT

Aluminum Tenders



Overal Beam

Overal Length

9'6"/ 2.90m

Number of Chambers

Shaft Length : 15" / 38.1cm

: 5'6"/ 1.68m

Person Capacity : 5

RDC Design Category : C

Inside Length

: 6'11"/ 2.11m

Weight

: 95lb / 43kg

Inside Beam

: 2'6"/ 0.76m

Recommended HP : 8hp / 6.0kw

Tube Diameter

: 17"/ 0.43m

Maximum HP : 15hp / 11.2kw

A A ⋖⋖ μш

SH

⋖ Δш Ош

ے

S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels

- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Deck Drain with Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes ■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
 Maintenance Kit
- Owner's Manual

 - 3 Layer Reinforced Seams Rubber Protector on Full Length of Keel

Tube Chaps

- **Boat Cover**
- Chock Set

- Bow Step with Fold Down Stainless Steel Cleat
- Bow Locker/ Seat
- Lateral Fold Down Stainless Steel Cleat



21 Rowland Street. Slacks Creek. Qld 4127 Ph 3808 1988 www.marinesafe.com.au