8VL

Lightweight Fiberglass Tender



Overal Length Overal Beam Inside Length

Inside Beam

ے

2

⋖⋖

 \vdash \sqcup

SH

Δш Ош : 8'6"/ 2.60m

Number of Chambers : 3 + 1

Shaft Length : 15" / 38.1cm

: 5'6"/ 1.68m

Person Capacity : 4 RDC Design Category : C

: 5′10″/ 1.79m

: 2'4"/ 0.72m Recommended HP

Weight

: 8hp / 6kw

: 95lb / 43kg

Tube Diameter : 16"/ 0.40m Maximum HP

: 10hp / 7.5kw

- Hand Laid Fiberglass Deep "V" Hull Stringer System Laminated into Hull Non Skid Rubber Floor Pannels

- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
 Stainless Steel Bow Eye
 Stainless Steel 3 Davit Lifting Points
- Stainless Steel 3 Davit Lifti
 Inner Hull Drain with Plug

- **Deck Condensation Plug**
- Orca(CSM) Five Layer Coated Fabric Raised Single Rub Rail

- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
- Removable Rowing Seat

- Oarlock Bases Telescopic Oars with Aluminum Shaft

- Hand Pump
 Maintenance Kit
 Owner's Manual
 Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

Tube Chaps

- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat



21 Rowland Street, Slacks Creek. Qld 4127 Ph 3808 1988 www.marinesafe.com.au

9VL

Lightweight Fiberglass Tender



Overal Beam

Overal Length

9'6"/2.90m

Number of Chambers : 3+1

Shaft Length : 15"/38.1cm

: 5′7″/ 1.72m

Person Capacity : 4 RDC Design Category : C

Inside Length

: 6'9"/ 2.06m

Weight

: 106lb / 48kg

Inside Beam

: 2'8"/ 0.81m

Recommended HP : 9.9hp / 7.4kw

Tube Diameter

: 17"/ 0.43m

Maximum HP : 15hp / 11.2kw

⋖ ΗШ

SН

 \circ

ΔШ ОШ

S

- Hand Laid Fiberglass Deep "V" Hull Stringer System Laminated into Hull
- Non Skid Rubber Floor Pannels
- Plastic External Transom Plate Aluminum Internal Transom Plate with Security Lip Stainless Steel Bow Eye Stainless Steel 3 Davit Lifting Points

- Inner Hull Drain with Plug

- Deck Condensation Plug Orca(CSM) Five Layer Coated Fabric Raised Single Rub Rail

- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases Telescopic Oars with Aluminum Shaft

- Hand Pump Maintenance Kit
- Owner's Manual Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

Tube Chaps

- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat



21 Rowland Street, Slacks Creek. Qld 4127 Ph 3808 1988 www.marinesafe.com.au

10VL

Lightweight Fiberglass Tender



Overal Beam

Overal Length

: 10'6"/3.19m

Number of Chambers : 3+1

Shaft Length : 15" / 38.1cm

: 5'7"/1.72m

Person Capacity : 5 RDC Design Category : C

Inside Length

: 7′7″/ 2.31m

Weight

: 123lb / 56kg

Inside Beam

: 2'8"/ 0.81m

Recommended HP : 15hp / 11.2kw

Tube Diameter

: 17"/ 0.43m

Maximum HP : 25hp / 18.7kw

4 4 \vdash \sqcup SП

- Hand Laid Fiberglass Deep "V" Hull Stringer System Laminated into Hull
- Non Skid Rubber Floor Pannels Plastic External Transom Plate
- ${\bf Aluminum\ Internal\ Transom\ Plate\ with\ Security\ Lip}$
- Stainless Steel Bow Eye Stainless Steel 3 Davit Lifting Points
- Inner Hull Drain with Plug

- Deck Condensation Plug Orca(CSM) Five Layer Coated Fabric

- Raised Single Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
 2 Inside Stern Set of 2 Orca(CSM) Fabric Handles on Tubes
- Removable Rowing Seat

- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Hand Pump
- Maintenance Kit Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat



21 Rowland Street, Slacks Creek. Qld 4127 Ph 3808 1988 www.marinesafe.com.au

؎

S

12VL

Lightweight Fiberglass Tender



S

Overal Length : 12′/ 3.66m Number of Chambers : 3 + 1Shaft Length : 15" / 38.1cm **Overal Beam** : 5′11″/ 1.77m **Person Capacity** : 6 RDC Design Category : C

Inside Length Weight : 8'9"/ 2.67m : 156lb / 71kg

Inside Beam : 2'9"/ 0.84m Recommended HP : 20hp / 14.9kw

Maximum HP Tube Diameter : 18"/ 0.46m : 30hp / 22.4kw

ж ш A A ⋖ ∟ ш SН

Ош

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Non Skid Rubber Floor Pannels
- Plastic External Transom Plate
 Aluminum Internal Transom Plate with Security Lip
- Stainless Steel Bow Eye Stainless Steel 3 Davit Lifting Points
- Inner Hull Drain with Plug

- Deck Condensation Plug Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes

 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes

- 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes

- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit Owner's Manual
- Additional Air Retaining Chamber Under the Floor 3 Layer Reinforced Seams

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat



21 Rowland Street, Slacks Creek. Qld 4127 Ph 3808 1988

www.marinesafe.com.au